



Caltrans Type "B" Profile

Armored Blockout Condition

Design Features

Cost effective solution with over 30 years history of success.

Wabo®PrimaLub lubricant facilitates the installation of the system.

Conforms to various structural configurations.

Proven profile design provides uniform compression and prevents the seal from being forced out of the joint opening.

Model	Groove Width "A"						Min. Install Width		Groove Depth "B"		Nominal			
	Min.		Max.		Total						Width		Height	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm
WA-175	0.668	17	1.488	38	0.800	20	1.000	25	2.625	67	1.750	44	1.625	41
WA-275	0.996	25	2.330	59	1.330	34	1.625	41	3.125	79	2.750	70	2.625	67
WA-375	1.720	44	3.300	84	1.580	40	2.375	60	4.250	108	3.875	98	3.750	95
WA-500	1.625	41	4.250	108	2.625	67	3.000	76	5.500	140	5.000	127	5.000	127
WA-600	2.000	51	5.100	130	3.100	79	3.500	89	6.500	165	6.000	152	6.000	152

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®CompressionSeal

DATE: 05-08-24

MODEL: WA



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:
2

SHEET NO:
2

DRAWING NO:
C-20513